






## Index for Function

### Motorless Model

Type	Photo	Model	Outlined specifications		Minimum packing unit (pcs) ※1, ※2	Page	
			Travel (mm)	Number of resistor elements			
Master type (K fader)		RS60K11	60	Single-unit	100	134	
		RSA0K11	100				
		RSA0K12		Dual-unit			
Low-profile master type (N fader)		RS60N11	60	Single-unit		100	138
		RSA0N11	100				
		RS60N12	60	Dual-unit			
		RSA0N12	100				
Low-profile master type (Slim type)		RS60N11S	60	Single-unit	100		142
		RSA0N11S	100				
Low-profile master type (Super Y fader)		RS6011SY	60	Dual-unit		100	145
		RS6011DY					

### Motor-driven Model

Type	Photo	Model	Outlined specifications		Minimum packing unit (pcs) ※1, ※2	Page
			Travel (mm)	Number of resistor elements		
Motor-driven master type (Motor K fader) (Motor N fader)		RSA0K11V	100	Single-unit (CP type)	100	148
		RS60N11M	60	Single-unit		
	RSA0N11M	100				

- Slide Volume Control for Mixers Product Specifications .....154
- Slide Volume Control Operations Cautions .....155, 156

### Notes

1. Attenuation is specified for residual resistance.
2. ※1. Please place purchase order per minimum packing unit.
3. ※2. Please contact us for export packing details.

